

1A, 400-600V Rectifiers

FEATURES

- Surface mount device type
- Low peakage current
- Compliant to RoHS directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- The devices are designed for high frequency miniatures switched Mode power supplies such as adapters, lighting and on-board DC/DC converters.

MECHANICAL DATA

- Case: SOD-123 small outline plastic package
- Molding compound meets UL 94 V-0 flammability rating
- Moisture sensitivity level: level 1, per J-STD-020
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Polarity: Indicated by cathode band
- Weight: 9.5 mg (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
$I_{F(AV)}$	1	A
V_{RRM}	400-600	V
I_{FSM}	7.5	A
V_F at $I_F=1A$	1.1	V
T_{JMAX}	150	°C
Package	SOD-123	
Configuration	Single dice	



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)				
PARAMETER	SYMBOL	2CZ4004	2CZ4005	UNIT
Marking code on the device		Z44	Z45	
Non-repetitive peak reverse voltage @ $I_R=100\mu\text{A}$	V_{RRM}	400	600	V
RMS reverse voltage	$V_{R(RMS)}$	280	420	V
Forward current	I_O	1		A
Non-repetitive peak forward surge current 8.3ms half sine wave	I_{FSM}	7.5		A
Power dissipation	P_D	350		mW
Junction temperature range	T_J	- 55 to +150		°C
Storage temperature range	T_{STG}	- 55 to +150		°C

THERMAL PERFORMANCE			
PARAMETER	SYMBOL	LIMIT	UNIT
Junction-to-ambient thermal resistance	$R_{\theta JA}$	357	°C/W

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)					
PARAMETER	CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage per diode ⁽¹⁾	$I_F = 1\text{A}, T_J = 25^\circ\text{C}$	V_F	-	1.1	V
Reverse current @ rated V_R per diode ⁽²⁾	$V_R = 400\text{V}, T_J = 25^\circ\text{C}$	I_R	-	5	μA
	$V_R = 600\text{V}, T_J = 25^\circ\text{C}$				
Junction capacitance	1 MHz, $V_R = 4\text{V}$	C_J	-	15	pF

Notes:

1. Pulse test with $PW = 0.3\text{ ms}$
2. Pulse test with $PW = 30\text{ ms}$

ORDERING INFORMATION				
PART NO. (Note. 1)	PACKING CODE	PACKING CODE SUFFIX	PACKAGE	PACKING
2CZ4004	RH	G	SOD-123	3K / 7" Reel
2CZ4005				

Notes:

1. Whole series with green compound

EXAMPLE				
EXAMPLE P/N	PART NO.	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
2CZ4004 RHG	2CZ4004	RH	G	Green compound

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig. 1 Typical Forward Characteristics




Fig. 2 Reverse Characteristics




Fig. 3 Capacitance Characteristics






Fig. 4 Power Derating Curve




PACKAGE OUTLINE DIMENSION



DIM.	Unit(mm)		Unit(inch)	
	Min	Max	Min	Max
A	1.40	1.80	0.055	0.071
B	3.55	3.85	0.140	0.152
C	0.45	0.70	0.018	0.028
D	2.55	2.85	0.100	0.112
E	0.95	1.35	0.037	0.053
F	0.05	0.15	0.002	0.006
G	0.50 REF		0.02 REF	
H	-	0.10	-	0.004

SUGGEST PAD LAYOUT



DIM.	Unit(mm)	Unit(inch)
	Min	Min
G	2.25	0.089
X	0.90	0.035
X1	4.05	0.159
Y	0.95	0.037

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.